



### Systems

# NetApp FAS3200 Series

Get advanced capabilities in a midrange storage system and easily respond to future expansion

### **KEY BENEFITS**

### Best value with unmatched efficiency.

The FAS3200 series delivers the advantages of the NetApp® unified storage architecture through one operating system, consistent management software, integrated data protection, multiple tiers of storage, and industry-leading storage efficiency.

## Increase flexibility and expand your environment.

The FAS3200 series scales to nearly 2PB plus has the extra PCIe slot connectivity you need to adapt to growing storage workloads.

Confidently deploy diverse workloads with enterprise-class availability and performance.

The FAS3200 series is designed for faster performance and more bandwidth with proven NetApp availability.

### THE CHALLENGE

There is an ongoing challenge to efficiently meet the growing storage needs of business applications such as messaging, collaboration, file services, Web, office productivity, databases, and more. What is needed is storage that is both efficient and flexible with high-end availability and performance to effectively meet the challenges of virtualized and traditional IT environments.

### THE SOLUTION

With the NetApp FAS3200 series you can cost-effectively meet the storage needs of business applications in both virtual and traditional environments. Handle today's workloads with industry-leading storage efficiency through the NetApp unified architecture running our Data ONTAP® storage operating system. Consolidate diverse data sets plus be ready to respond to change more easily and non-disruptively with the extra PCle slots, high performance, and enterprise-class availability of the FAS3200 series.

Midsize environments can gain high-end benefits without the budget or space required to support frame-array-class systems. Regional data centers, replicated sites, and departmental systems that need full-featured, yet efficient, storage with advanced availability and performance capabilities can benefit too.

The FAS3200 series spans three models to enable you to tailor-fit a solution that's right for your environment: FAS3210, FAS3240, and FAS3270. Our systems are simple to install, provision, and upgrade to meet your needs. Plus you can maximize productivity with our common suite of application-aware management software. The FAS3200 systems, with the best value for mixed workloads, can give you an edge that other midrange storage platforms simply cannot match.

### LOWER COSTS WITH OUR HIGHLY EFFICIENT SYSTEMS

NetApp delivers a truly unified storage architecture that uses a single platform with common software and processes across all tiers of storage. You can consolidate your diverse workloads with multi-protocal support and also benefit from integrated data protection, one operating system across the entire family, and heterogenous disk array support with V-series. This helps you maximize the efficiency of your virtual servers by delivering storage when and where it's needed.

What's more, common management across our unified storage architecture assists in consolidation of diverse data sets and data-in-place controller upgrades to more powerful FAS systems. This lowers your administrative costs and makes it easier for you to deploy new capabilities across your enterprise.

The FAS3200 series enables you to build a flexible and efficient shared infrastructure today as your foundation for future-ready IT.



Figure 2) NetApp FAS3200 controller.

If you are looking to dramatically decrease your consumption of space, power, and cooling, then deploy your FAS3200 series system with our DS2246 disk shelf. This leading-edge disk shelf features the latest SAS technology using small-form-factor SAS 2.5" disk drives capable of doubling capacity per rack unit, conserving your valuable data center resources.

#### **INCREASE FLEXIBILITY**

The FAS3200 series scales to nearly 2PB of versatile storage that adapts readily to your growing storage demands. If your environment needs extra connectivity, the expanded I/O configurations of the FAS3240 and FAS3270 models significantly add to the number of PCIe expansion slots available. Moreover, all FAS3200 systems support Data ONTAP in both standard and cluster modes, providing you with the flexibility of up to 24 nodes.

### GET PROVEN AVAILABILITY AND PERFORMANCE

The FAS3200 series is built on the proven enterprise-class availability of the NetApp storage infrastructure. The FAS3200 models leverage from high-end systems by introducing features such as Alternate Control Path (ACP) and service processor. These enhance our already highly available architecture by enabling additional diagnostics and non-disruptive recovery.

You can further boost data availability and get zero planned and unplanned downtime by combining the FAS3200 series with our MetroCluster™ solution, which promotes continuous access to data and prevents data loss. MetroCluster delivers distance array-based clustering to protect against outages within your data center, across campus, or citywide due to hardware failures, power, network, and environmental faults.

The FAS3200 series features leading-edge technology for high-performance storage. Use our DS4243 with solid state drives (SSDs) when every I/O read must be fast. Or boost system performance by adding up to 2TB of Flash Cache. These intelligent caching modules automatically increase read rates and reduce average latency for your frequently accessed data, without adding more disk drives. Our Flash Cache combined with hard disk drives is an effective and typically more affordable alternative to SSDs.

### INDUSTRY-LEADING STORAGE EFFICIENCY WITH DATA ONTAP

Data ONTAP is our storage operating system that delivers industry-leading storage efficiency across our unified architecture.

- Expand or contract LUNs or volumes instantly with thin provisioning to keep storage operations as lean as possible.
- High-efficiency NetApp Integrated Data Protection reduces the cost and complexity of safeguarding your business.
- Space-efficient Snapshot<sup>™</sup> copies enable more frequent local backups and restores in minutes.
- Thin replication enables backup and recovery, disaster recovery, and archival using minimal storage capacity and network resources.
- Likewise, our low-overhead double-parity RAID-DP® offers better data protection and capacity utilization than traditional RAID implementations.
- Add to this our NetApp deduplication and data compression, which provide the industry's best answer to ever-increasing storage capacity demands, and you can dramatically increase the efficiency of your storage and lower TCO.

FAS3200 TECHNICAL SPECIFICATIONS
All data in this table applies to active-active dual controller configurations.

	FAS3270 with Expanded I/O	FAS3270	FAS3240 with Expanded I/O	FAS3240	FAS3210	
Maximum Raw Capacity	1920TB	1920TB	1200TB	1200TB	480TB	
Maximum Disk Drives	960	960	600	600	240	
Controller Form Factor	Dual enclosure HA; 2 controllers in two 3U chassis, total of 6U	Single enclosure HA; 2 controllers in single 3U chassis	Dual enclosure HA; 2 controllers in two 3U chassis, total of 6U	Single enclosure HA; 2 controllers in single 3U chassis	Single enclosure HA; 2 controllers in single 3U chassis	
Memory	32GB	32GB	16GB	16GB	8GB	
Flash Cache (maximum)	2TB	2TB	1TB	1TB	512GB	
PCIe Expansion Slots	12	4	12	4	4	
Onboard I/O: 4Gb FC	4	4	4	4	4	
Onboard I/O: 6Gb SAS	4	4	4	4	4	
Onboard I/O: GbE	4	4	4	4	4	
Storage Networking Supported	FC; FCoE; IP SAN	(iSCSI); NFS; CIFS;	HTTP; FTP			
OS Version	Data ONTAP 8					
Supported Configurations  Disk Shelves Supported	Highly available controller configurations:     Active-active controller with controller failover and multi-path HA storage     Active-active controller with stretch (nonswitch) and fabric-attached MetroCluster V-Series Storage Acceleration Appliance SA320  DS2246 (2U; 24 drives – 2.5" SAS SFF) DS4243 (4U; 24 drives – 3.5" SATA/SAS/SSD)					
Maximum RAID Group Sizes	DS14mk2 and DS14mk4 (3U; 14 drives, 3.5" FC/SATA)  RAID 6 (RAID-DP): FC – 28 (26 data disks plus 2 parity disks)  SATA – 20 (18 data disks plus 2 parity disks)					
	RAID 4: FC – 14 (* SATA – 7	13 data disks plus 1 (6 data disks plus 1	parity disk)	ionoj		
Operating Systems Supported	Windows® 2000, Windows Server 2003, Windows Server 2008, Windows XP, Linux®, Sun Solaris, AIX, HP-UX, Mac® OS, VMware®, ESX					
Operating Systems Supported	AIX, HP-UX, Mac®	OS, VMware®, ESX	o, Willdows Server 20	JUB, WINDOWS XP, LI	inux®, Sun Solaris,	
	AIX, HP-UX, Mac <sup>®</sup>	OS, VMware <sup>®</sup> , ESX	5, Williaows Server 20	506, Windows XP, Li	inux®, Sun Soiaris,	
Maximum Number of LUNs	AIX, HP-UX, Mac <sup>®</sup> 4096 Up to 512 hosts pe	OS, VMware <sup>®</sup> , ESX		Juo, Windows AP, Li	inux°, Sun Solaris,	
Maximum Number of LUNs Number of Supported SAN Hosts	AIX, HP-UX, Mac <sup>®</sup> 4096 Up to 512 hosts pe	OS, VMware®, ESX er HA pair onnected servers pe		Juo, Williaows AP, Li	inux°, Sun Solaris,	
Maximum Number of LUNs Number of Supported SAN Hosts FlexVol® Volumes Snapshot Copies	AIX, HP-UX, Mac® 4096 Up to 512 hosts pour to 24 directly c	OS, VMware®, ESX er HA pair onnected servers pe		Juo, Williaows AP, Li	inux°, Sun Solaris,	
Maximum Number of LUNs Number of Supported SAN Hosts FlexVol® Volumes Snapshot Copies	AIX, HP-UX, Mac® 4096  Up to 512 hosts pour to 24 directly country to 500 per constitution.	OS, VMware®, ESX er HA pair onnected servers pe		50TB	50TB	
Maximum Number of LUNs Number of Supported SAN Hosts FlexVol® Volumes Snapshot Copies Maximum Volume/Aggregate Size	AIX, HP-UX, Mac® 4096 Up to 512 hosts pup to 24 directly cup to 500 per conup to 127,000 70TB	OS, VMware®, ESX er HA pair onnected servers pe troller 70TB	er HA pair 50TB			
Maximum Number of LUNs Number of Supported SAN Hosts FlexVol® Volumes Snapshot Copies Maximum Volume/Aggregate Size Maximum Port Count Includes Integ	AIX, HP-UX, Mac® 4096 Up to 512 hosts pup to 24 directly cup to 500 per conup to 127,000 70TB	OS, VMware®, ESX er HA pair onnected servers pe troller 70TB	er HA pair 50TB			
Maximum Number of LUNs Number of Supported SAN Hosts FlexVol® Volumes Snapshot Copies Maximum Volume/Aggregate Size Maximum Port Count Includes Integ FC Target Ports (8Gb/4Gb) (max)	AIX, HP-UX, Mac® 4096  Up to 512 hosts pour to 24 directly computed to 500 per computed to 127,000 70TB  grated Ports and PC	OS, VMware®, ESX er HA pair onnected servers pe troller 70TB le Expansion Slots	er HA pair 50TB	50TB	50TB	
Maximum Number of LUNs Number of Supported SAN Hosts FlexVol® Volumes Snapshot Copies Maximum Volume/Aggregate Size Maximum Port Count Includes Integ FC Target Ports (8Gb/4Gb) (max) 10GbE, FCoE Target Ports (max)	AIX, HP-UX, Mac® 4096 Up to 512 hosts put to 24 directly cup to 500 per contup to 127,000 70TB grated Ports and PC 24/52	OS, VMware®, ESX er HA pair onnected servers petroller  70TB le Expansion Slots 8/20	or HA pair 50TB 24/52	50TB 8/20	50TB 8/20	
Maximum Number of LUNs Number of Supported SAN Hosts FlexVol® Volumes Snapshot Copies Maximum Volume/Aggregate Size Maximum Port Count Includes Integ FC Target Ports (8Gb/4Gb) (max) 10GbE, FCoE Target Ports (max) GbE Ports (max)	AIX, HP-UX, Mac® 4096  Up to 512 hosts pr Up to 24 directly c Up to 500 per con Up to 127,000 70TB  grated Ports and PC 24/52	OS, VMware®, ESX er HA pair onnected servers pe troller  70TB le Expansion Slots 8/20 8	50TB 24/52 24	50TB 8/20 8	50TB 8/20 8	
Maximum Number of LUNs Number of Supported SAN Hosts FlexVol® Volumes Snapshot Copies Maximum Volume/Aggregate Size Maximum Port Count Includes Integ FC Target Ports (8Gb/4Gb) (max) 10GbE, FCoE Target Ports (max) GbE Ports (max) 6Gb SAS Ports (max)	AIX, HP-UX, Mac® 4096  Up to 512 hosts pure up to 24 directly complete up to 500 per confunction up to 127,000 70TB  grated Ports and PC 24/52 24 521	OS, VMware®, ESX er HA pair onnected servers pe troller  70TB le Expansion Slots 8/20 8 20	50TB 24/52 24 52 <sup>1</sup>	50TB 8/20 8 20	50TB 8/20 8 20	
Maximum Number of LUNs Number of Supported SAN Hosts FlexVol® Volumes Snapshot Copies Maximum Volume/Aggregate Size Maximum Port Count Includes Integ FC Target Ports (8Gb/4Gb) (max) 10GbE, FCoE Target Ports (max) GbE Ports (max) FC Initiator Ports (max)	AIX, HP-UX, Mac® 4096  Up to 512 hosts purely to 24 directly curve to 500 per conformation. Up to 127,000 70TB  grated Ports and PC 24/52 24 521 52	OS, VMware®, ESX er HA pair onnected servers per troller  70TB le Expansion Slots 8/20 8 20 20	50TB  24/52 24 52 <sup>1</sup> 52	50TB 8/20 8 20 20	50TB 8/20 8 20 20	
Maximum Number of LUNs Number of Supported SAN Hosts FlexVol® Volumes Snapshot Copies Maximum Volume/Aggregate Size Maximum Port Count Includes Integ FC Target Ports (8Gb/4Gb) (max) 10GbE, FCoE Target Ports (max) GbE Ports (max) GGb SAS Ports (max) FC Initiator Ports (max) Maximum Adapters	AIX, HP-UX, Mac® 4096  Up to 512 hosts purely to 24 directly curve to 500 per conformation. Up to 127,000 70TB  grated Ports and PC 24/52 24 521 52	OS, VMware®, ESX er HA pair onnected servers per troller  70TB le Expansion Slots 8/20 8 20 20	50TB  24/52 24 52 <sup>1</sup> 52	50TB 8/20 8 20 20	50TB 8/20 8 20 20	
Maximum Number of LUNs Number of Supported SAN Hosts FlexVol® Volumes Snapshot Copies Maximum Volume/Aggregate Size Maximum Port Count Includes Integ FC Target Ports (8Gb/4Gb) (max) 10GbE, FCoE Target Ports (max) GbE Ports (max) GbE SAS Ports (max) FC Initiator Ports (max) Maximum Adapters Dual 10GbE (optical or copper)	AIX, HP-UX, Mac® 4096 Up to 512 hosts put to 24 directly cup to 500 per conumber 127,000 70TB grated Ports and PC 24/52 24 521 52 52	OS, VMware®, ESX er HA pair connected servers per troller  70TB le Expansion Slots 8/20 8 20 20 20	50TB  24/52 24 521 52 52	50TB 8/20 8 20 20 20	50TB 8/20 8 20 20 20	
Maximum Number of LUNs Number of Supported SAN Hosts FlexVol® Volumes Snapshot Copies Maximum Volume/Aggregate Size Maximum Port Count Includes Integ FC Target Ports (8Gb/4Gb) (max) 10GbE, FCoE Target Ports (max) GbE Ports (max) GbE SAS Ports (max) FC Initiator Ports (max) Maximum Adapters Dual 10GbE (optical or copper) Quad GbE (copper) Dual 10GbE FCoE SAN Unified	AIX, HP-UX, Mac® 4096  Up to 512 hosts pr Up to 24 directly c  Up to 500 per con  Up to 127,000  70TB  grated Ports and PC 24/52 24 52¹ 52 52	OS, VMware®, ESX er HA pair connected servers pe troller  70TB le Expansion Slots 8/20 8 20 20 20	50TB  24/52 24 52¹ 52 52	50TB 8/20 8 20 20 20	50TB 8/20 8 20 20 20	
Maximum Number of LUNs Number of Supported SAN Hosts FlexVol® Volumes Snapshot Copies Maximum Volume/Aggregate Size Maximum Port Count Includes Integ FC Target Ports (8Gb/4Gb) (max) 10GbE, FCoE Target Ports (max) GbE Ports (max) 6Gb SAS Ports (max) FC Initiator Ports (max) Maximum Adapters Dual 10GbE (optical or copper) Quad GbE (copper) Dual 10GbE FCoE SAN Unified Target Adapter (optical or copper)	AIX, HP-UX, Mac® 4096  Up to 512 hosts pr Up to 24 directly c  Up to 500 per con  Up to 127,000  70TB  grated Ports and PC 24/52 24 52¹ 52 52 12 12 12¹	OS, VMware®, ESX er HA pair connected servers pe troller  70TB le Expansion Slots 8/20 8 20 20 20 4 4	50TB  24/52 24 52¹ 52 52 12 12¹	50TB 8/20 8 20 20 20 4 4	50TB 8/20 8 20 20 20 4	
Maximum Number of LUNs Number of Supported SAN Hosts FlexVol® Volumes Snapshot Copies Maximum Volume/Aggregate Size Maximum Port Count Includes Integ FC Target Ports (8Gb/4Gb) (max) 10GbE, FCoE Target Ports (max) GbE Ports (max) GCB SAS Ports (max) FC Initiator Ports (max) Maximum Adapters Dual 10GbE (optical or copper) Quad GbE (copper) Dual 10GbE FCoE SAN Unified Target Adapter (optical or copper) BGB FC Target (optical)	AIX, HP-UX, Mac® 4096  Up to 512 hosts pr Up to 24 directly c  Up to 500 per con  Up to 127,000  70TB  grated Ports and PC 24/52 24 52¹ 52 52 12 12 12¹ 12	OS, VMware®, ESX er HA pair connected servers pe troller  70TB le Expansion Slots 8/20 8 20 20 20 4 4 4	50TB  24/52 24 52¹ 52 52 12 12 12¹ 12¹	50TB  8/20 8 20 20 20 4 4 4	50TB  8/20 8 20 20 4 4 4	
Maximum Number of LUNs Number of Supported SAN Hosts FlexVol® Volumes	AIX, HP-UX, Mac® 4096  Up to 512 hosts pr Up to 24 directly c  Up to 500 per con  Up to 127,000  70TB  grated Ports and PC 24/52 24 52¹ 52 52 12 12 12¹ 12	OS, VMware®, ESX er HA pair connected servers pe troller  70TB le Expansion Slots 8/20 8 20 20 4 4 4	50TB  24/52 24 52¹ 52 52 12 12 12¹ 12	50TB  8/20 8 20 20 4 4 4 4	50TB  8/20 8 20 20 4 4 4 4	
Maximum Number of LUNs Number of Supported SAN Hosts  FlexVol® Volumes Snapshot Copies Maximum Volume/Aggregate Size Maximum Port Count Includes Integ FC Target Ports (8Gb/4Gb) (max) 10GbE, FCoE Target Ports (max) GbE Ports (max) 6Gb SAS Ports (max) FC Initiator Ports (max) Maximum Adapters Dual 10GbE (optical or copper) Quad GbE (copper) Dual 10GbE FCoE SAN Unified Target Adapter (optical or copper) 8Gb FC Target (optical) Dual 8Gb VI FC for SnapMirror® Flash Cache (PAM II) (512GB)	AIX, HP-UX, Mac® 4096  Up to 512 hosts pr Up to 24 directly c Up to 500 per con Up to 127,000 70TB  grated Ports and PC 24/52 24 52¹ 52 52 12 12 12 12 12	OS, VMware®, ESX er HA pair connected servers pe troller  70TB le Expansion Slots 8/20 8 20 20 20 4 4 4 4	50TB  24/52 24 52¹ 52 52 12 12 12¹ 12 12 2	50TB  8/20 8 20 20 20 4 4 4 4 2	50TB  8/20 8 20 20 4 4 4 4 2	
Maximum Number of LUNs Number of Supported SAN Hosts FlexVol® Volumes Snapshot Copies Maximum Volume/Aggregate Size Maximum Port Count Includes Integ FC Target Ports (8Gb/4Gb) (max) 10GbE, FCoE Target Ports (max) GbE Ports (max) GbE SAS Ports (max) FC Initiator Ports (max) Maximum Adapters Dual 10GbE (optical or copper) Quad GbE (copper) Dual 10GbE FCoE SAN Unified Target Adapter (optical or copper) BGB FC Target (optical) Dual 8Gb VI FC for SnapMirror®	AIX, HP-UX, Mac® 4096  Up to 512 hosts pr Up to 24 directly c  Up to 500 per con  Up to 127,000  70TB  grated Ports and PC 24/52 24 52¹ 52 52 12 12 12¹ 12 12 2 4	OS, VMware®, ESX er HA pair connected servers pe troller  70TB le Expansion Slots 8/20 8 20 20 20 4 4 4 4 4	50TB  24/52 24 52¹ 52 52 12 12 12¹ 12 2	50TB  8/20 8 20 20 20 4 4 4 2 2	50TB  8/20 8 20 20 4 4 4 4 7	

<sup>1</sup> Maximum number of GbE ports & adapters depends on the Data ONTAP release in use

### **FAS3200 SERIES SOFTWARE**

The FAS3200 includes a simplified software structure that offers more value and enhanced simplicity while maintaining a flexible foundation for building custom solutions.

As reflected below, enhancements include:

- More software value is now included standard with every system via Data ONTAP Essentials
- A-la-carte structure of add-on software simplified to five key software products
- Customers have the flexibility to select one protocol of their choice to be included with the base system (other protocols can be added separately)
- A Complete Bundle of all NetApp Extended Value software is available for all-inclusive functionality and convenience

#### **DATA ONTAP ESSENTIALS**

The following software is included with every FAS/V3200 system, delivering unmatched value through greater flexibility, availability, and automation:

Product/Feature	Description	
System Manager	Windows OS-based management tool for single system deployment	
Operations Manager	Deploy, provision, monitor and manage multiple NetApp storage systems.	
Provisioning Manager	Policy-based automation software for provisioning NetApp SAN and NAS.	
Protection Manager	Policy-based automation software for backup and recovery operations.	
SyncMirror	Maintains two local, online copies of data. Protects against all types of hardware outages.	
MetroCluster	Combines array-based clustering with synchronous mirroring; provides continuous availability at a low cost.	
Deduplication	Transparently removes duplicate data at the block level, for all storage tiers.	
Thin provisioning	Enables on-demand storage provisioning to achieve maximum utilization across multiple applications.	
FlexVol	Enables virtual volumes that you can manage and move independently from physical storage.	
RAID-DP	Safeguards your data from double disk failure, with no performance penalty.	
Snapshot	Enables quick point-in-time copies of file systems or LUNs; NetApp Snapshot uniquely carries no performance penalty.	
Open Systems SnapVault	Backup of DAS connected to Windows or UNIX servers; maintains online archive of backup copies.	
MultiStore	Secure partitioning of network and storage resources enables consolidation of multiple domains on a single system.	
FlexCache	Enables NetApp systems to be used as caches.	
FlexShare	Automatically allocates storage resources to higher priority workloads.	
Included SAN or NAS protocol	One SAN or NAS protocol of your choice (iSCSI, FC, NFS, CIFS) is included with your system.	
	System Manager Operations Manager Provisioning Manager Protection Manager SyncMirror MetroCluster  Deduplication Thin provisioning  FlexVol  RAID-DP Snapshot  Open Systems SnapVault MultiStore  FlexCache FlexShare Included SAN or	

### **Extended-Value Software:**

Affordable, easy to buy add-on software modules are available to enhance base system functionality. These can be purchased individually, or all of these products can be purchased together via the NetApp Complete Bundle.

Capability	Product/Feature	Description
Application Integration	SnapManager <sup>®</sup> Suite	Enables application aware and virtual machine aware backup, recovery, and cloning (for Oracle, Exchange, SharePoint, SQL, SAP, Virtual Infrastructure, and Hyper-V).
System Recovery	SnapRestore®	Restore LUNs and file systems from previously backed-up snapshot copies in seconds, irrespective of size or number of files.
Disaster Recovery	SnapMirror <sup>®</sup>	Synchronous, semi-synchronous, and asynchronous data replication soft- ware that delivers simple, efficient, and flexible disaster recovery for busi- ness-critical applications.
Virtual Cloning	FlexClone <sup>®</sup>	Instantly create transparent virtual copies of production databases or virtual machines, without needing any additional storage capacity or compromising performance.
Disk-to-disk Backup	SnapVault <sup>®</sup>	Disk-to-disk backup software for complete back-ups and online archives to primary or secondary storage in minutes instead of hours or days.
Storage Protocols	Optional SAN and NAS protocols	Native support for all key SAN/NAS protocols (iSCSI, FC, NFS, CIFS), makes NetApp systems ideal for consolidating your mixed IT environment. One protocol of your choice is included standard with your system; others can be added as desired.
All Extended Value Software	Complete Bundle	All of the Extended Value software above, together in a single bundle for all-inclusive convenience.

#### FAS3200 SERIES QUICK CHECKLIST FOR ORDERING

Models	FAS3270 FAS3240 FAS3210
Flash Cache (PAM II)	512GB and 256GB modules
I/O Options	Optional NICs and HBAs
Disk Shelves	DS2246 (24 drives – 2.5" SAS SFF) DS4243 (24 drives – 3.5" SATA/SAS/SSD) DS14mk2 and DS14mk4 (for MetroCluster and DC configurations; 14 drives – 3.5" FC/SATA)
Storage Protocols	FC, IP SAN (iSCSI), NFS, CIFS
Optional Software	Refer to FAS3200 series software tables
Professional Services	Storage System Installation Service, RDS+ Implementation Services, Storage Controller Upgrade Service, Assessment Services, Consulting Services, Deployment/Implementation Services, Managed Services, Solution Suites
Support	SupportEdge Services

### **PROFESSIONAL SERVICES**

Modular offerings customized for you NetApp Professional Services can assist you in any and every phase of the storage lifecycle. Whether you need help planning your next-generation storage system, need an extra set of hands for a major storage deployment, or want to upgrade your existing infrastructure, NetApp Professional Services personnel have the skills and expertise. NetApp offers a complete portfolio of services. In summary, NetApp Professional Services offerings include:

- Solution Suites: These customized solutions are designed to address your business-level challenges holistically.
- Assessment Services: Enlist NetApp to identify and document business, storage, and infrastructure requirements and receive recommendations for improvements.
- Consulting Services: Reduce the complexity of your networked storage implementation when you enlist our

experts to design, document, and implement a range of applications and solutions.

- Deployment/Implementation Services:
   Reduce risk as we prepare your site, install
   and connect systems, set up your software, and perform complete verification.
- Managed Services: Have NetApp experts on site to perform storage management services so you can focus on core business initiatives.

#### **GLOBAL SUPPORT**

### SupportEdge services

NetApp Global Support delivers the highest availability for your enterprise data environment and helps you optimize your storage investments. Let NetApp mitigate support issues and drive operational best practices. NetApp's innovative, proactive support means you'll have fewer and less-severe support cases. But if a problem arises, our award-winning technical centers and field support staff—delivering in over 100 countries—won't rest until it's solved.

As an industry leader in innovation, NetApp Global Support provides tools and technology to enable business continuity. AutoSupport™, NetApp's suite of automation tools, is delivered as a service to help you proactively manage your systems and quickly resolve issues. AutoSupport functions as a "virtual staff" to protect critical data, save time, and reduce impact on your IT resources.

### **ABOUT NETAPP**

NetApp creates innovative storage and data management solutions that help you accelerate business breakthroughs and achieve outstanding cost efficiency. Discover our passion for helping companies around the world go further, faster at netapp.com. For more information go to:

- FAS3200 system: www.netapp.com/us/ products/storage-systems/fas3200/
- Additional products and software: www.netapp.com/us/products/
- Professional Services: www.netapp.com/ us/services/professional/
- Support: www.netapp.com/us/support/



© Copyright 2010, NetApp, Inc. All rights reserved. No portions of this document may be reproduced without prior written consent of NetApp, Inc. Specifications are subject to change without notice. NetApp, the NetApp logo, Go further faster, AutoSupport, Data ONTAP, FlexCache, FlexClone, FlexShare, FlexVol, MetroCluster, MultiStore, RAID-DP, SnapDrive, SnapManager, SnapMiror, SnapRestore, Snapshot, SnapVault, and SyncMirror are trademarks or registered trademarks of NetApp, Inc. in the United States and/or other countries. Linux is a registered trademark of Inc. of the Countries. Linux is a registered trademark of The Open Group. Oracle is a registered trademark and Hyper-V is a trademark of Microsoft Corporation. UNIX is a registered trademark of Apple Inc. Whware is a registered trademark of The Open Group. Oracle is a registered trademark of The Open Group. Oracle is a registered trademark of Oracle Corporation. SAP is a registered trademark of SAP AG. Mac is a registered trademark of Apple Inc. Whware is a registered trademark of the Vivare, Inc. All other brands or products are trademarks or registered trademarks of their respective holders and should be treated as such. DS-3095-1110